

VERSOLEIL OUTRIGGER SUNSHADE
INSTALLATION INSTRUCTIONS
FOR 1600 SYSTEM 1

THE FOLLOWING INSTRUCTIONS ARE FOR THE
INSTALLATION OF THE KAWNEER VERSOLEIL OUTRIGGER
SUNSHADE. USE THESE INSTRUCTIONS IN CONJUNCTION
WITH 1600 SYSTEM 1 CURTAIN WALL INSTALLATION
INSTRUCTIONS (162970).

FRAME ASSEMBLY

VERTICAL MULLIONS WILL BE LABELED AND MUST BE
MATCHED TO SHOP DRAWINGS BEFORE PROCEEDING WITH
ANY ASSEMBLY. FAILURE TO PROPERLY ORIENT OR
POSITION THE VERTICAL MULLIONS WILL PROHIBIT
INSTALLATION OF THE SUNSHADE.

EXTERIOR COVERS

WHEN USING 1" COVERS, THE SUNSHADE ANCHOR CLIP
MUST BE INSTALLED BEFORE THE COVERS. THE
SUNSHADE IS TO BE INSTALLED AFTER THE COVERS.

WHEN USING OPTIONAL 3-1/8" COVERS, THE SUNSHADE
ANCHOR CLIP AND THE SUNSHADE MUST BE INSTALLED
BEFORE INSTALLING THE COVERS.



INSTALL 162310 THERMAL BREAK

INSTALLATION OF THE THERMAL BREAK ON HORIZONTAL
MEMBERS REMAINS UNCHANGED.

SUNSHADES REQUIRE THE USE OF TWO TONGUE FILLERS
(494211) AT EVERY ANCHOR CLIP LOCATION. CHECK SHOP
DRAWINGS FOR POSITION OF ANCHOR CLIPS. FOR EACH
LOCATION OF AN ANCHOR CLIP, THE VERTICAL MULLION
HAS BEEN PREPPED WITH THREE PILOT HOLES. RUN A
BEAD OF SEALANT ALONG THE MULLION TONGUE FACE AND
INTO THE SCREW BOSS AT EACH TONGUE FILLER LOCATION
AND TAP TONGUE FILLER INTO PLACE. ALIGN THE CLEAR
HOLES OF THE TONGUE FILLERS WITH THE THREE HOLES IN
THE MULLION. ADJUST TONGUE FILLER UNTIL HOLES ARE IN
THE PROPER ALIGNMENT. NOTE THAT SOME OF THE HOLES
IN THE TONGUE FILLERS WILL NOT BE USED. TOOL EXCESS
SEALANT. SEE DETAIL 1

INSERT THERMAL BREAK (162310) ALONG THE FULL LENGTH
OF THE VERTICAL MULLION TONGUE AND BUTT TO TONGUE
FILLER. SEE DETAIL 1. TRIM FLUSH AT TOP AND BOTTOM
OF TONGUE FILLER. DO NOT OVERLAP.

JUST PRIOR TO INSTALLING PRESSURE PLATES, PULL BACK
162310 THERMAL SEPARATOR AT TOP AND BOTTOM OF
TONGUE FILLERS AND RUN A BEAD OF SEALANT ACROSS
THE TOP AND BOTTOM OF THE TONGUE FILLER TO SEAL TO
THERMAL SEPARATORS. SEE DETAIL 2. BE SURE TO FILL
THE GAP BETWEEN THE "NOSE" OF THE TONGUE FILLER
AND THE GROOVE OF THE TONGUE. DO NOT ALLOW
SEALANT TO CURE PRIOR TO INSTALLING PRESSURE
PLATES.




INSTALL EXTERIOR PRESSURE PLATES

PRESSURE PLATES WILL BE PREPPED FOR THE SUNSHADES
PRIOR TO SHIPMENT TO THE JOB SITE. THE PREP WILL
CONSIST OF THREE CLEAR HOLES PER SUNSHADE
ATTACHMENT. CLEAR HOLES IN PRESSURE PLATE MUST BE
ALIGNED WITH CORRESPONDING HOLES IN TONGUE FILLER
AND MULLION. SEE DETAIL 3.

TO ENSURE ALIGNMENT, INSERT TWO 3/8" LAG SCREWS
(125531) THROUGH THE CENTER OF THE CLEAR HOLES IN
BOTH THE TOP AND BOTTOM POSITION AS TEMPORARIES
(FINGER TIGHTEN).

INSTALL PRESSURE PLATES, FOLLOWING STANDARD 1600
SYSTEM 1 INSTALLATION INSTRUCTIONS, USING 1/4 x 1" HEX
WASHER HEAD TYPE AB SCREWS (128406). USE ONLY
PRE-DRILLED HOLES IN PRESSURE PLATE AND APPLY ONLY
THROUGH THERMAL BREAK. **DO NOT SCREW INTO TONGUE
FILLER** (494211). REFERENCE STANDARD 1600 SYSTEM 1
INSTALLATION INSTRUCTIONS. REMOVE TEMPORARILY
APPLIED LAG SCREWS.



CONFIDENTIAL AND PROPRIETARY INFORMATION
KAWNEER COMPANY INC.

THESE DRAWINGS ARE THE SOLE AND EXCLUSIVE PROPERTY OF KAWNEER AND CONTAIN
SENSITIVE, PRIVILEGED OR CONFIDENTIAL INFORMATION WHICH MAY BE USED ONLY FOR ITS
BENEFIT. THE DISCLOSURE OF THESE DRAWINGS TO UNAUTHORIZED PERSONS IS STRICTLY
PROHIBITED. THIS DOCUMENT AND ALL COPIES MUST BE RETURNED UPON DEMAND.
© COPYRIGHT KAWNEER COMPANY, INC., 2011

SUNSHADE ATTACHMENT, TYPICAL
INTERMEDIATE

ATTACH ANCHOR CLIPS


ALIGN THE THREE CLEAR HOLES IN THE ANCHOR CLIP
(494200) WITH THE THREE HOLES IN THE PRESSURE PLATE
AND MULLION. ATTACH WITH THREE 3/8" x 2 1/2" LAG
SCREWS (128531) AND WITH THREE LOCK WASHERS
(028779). SEE DETAIL 4.

THE THREAD FORMING ACTION OF THE LAG SCREWS WILL
CAUSE ADDITIONAL RESISTANCE AND REQUIRE EXTRA
FORCE TO SEAT. APPLY A WAX LUBRICANT TO THE
THREADS BEFORE PROCEEDING.

**NOTE: DO NOT INCREASE HOLE SIZE TO FACILITATE
INSTALLATION.**

TIGHTEN BOLTS TO A "SNUG" CONDITION AND COMPLETELY
COMPRESS THE SPRING TYPE LOCK WASHERS. THEN
TIGHTEN APPROXIMATELY 1/2 TURN MORE.

ATTACH ALL ANCHOR CLIPS
BEFORE PROCEEDING TO
NEXT STEP.



VERSOLEIL OUTRIGGER
SUNSHADE
1600 SYSTEM 1
INSTALLATION INSTRUCTIONS


ASSEMBLING THE SUNSHADES

VERSOLEIL OUTRIGGER SUNSHADE BAY ASSEMBLIES USE SCREW SPLINE JOINERY. LAYOUT LEFT AND RIGHT OUTRIGGERS (JAMBS AT INSIDE CORNERS, AND SINGLE MULLION 90° OUTSIDE CORNERS ARE HANDED PARTS), BLADES, AND FASCIA PER SHOP DRAWINGS. SEE DETAILS 5 AND 6.

USING #12-24 x 1" PAN HEAD THREAD CUTTING SCREWS (128556), JOIN BLADES AND FASCIA COMPONENTS TO ONE OUTRIGGER. DO NOT TIGHTEN. ALIGN THE OPPOSITE OUTRIGGER AND CONNECT PARTS SIMILARLY. TIGHTEN BOTH SIDES.

NOTE: END ASSEMBLY REQUIRES A JAMB OUTRIGGER TO BE ATTACHED BEFORE INSTALLATION. USING #12 x 2 1/2" FLAT HEAD THREAD FORMING SCREWS (904197) AND APPROPRIATE TRIM FILLER, JOIN JAMB OUTRIGGER TO BAY ASSEMBLY. TIGHTEN UNTIL FULLY SEATED AND FLUSH WITH THE SURFACE OF THE JAMB OUTRIGGER. INSTALL ANCHOR CLIP FILLER (494201) USING (1) 3/8" x 2" HEX HEAD BOLT (128539) AND TEMPORARILY ATTACH (1) 3/8" HEX NUT (028780) TO SECURE JAMB OUTRIGGER DURING INSTALLATION. SEE DETAIL 6. CHECK SHOP DRAWINGS TO DETERMINE SPECIFIC JAMB CONDITION BEFORE PROCEEDING.



ASSEMBLE ALL OF THE VERSOLEIL OUTRIGGER SUNSHADE BAY ASSEMBLIES AND MARK OR TAG EACH ONE TO MATCH CORRESPONDING UNIT AS SHOWN ON SHOP DRAWINGS.



CONFIDENTIAL AND PROPRIETARY INFORMATION
KAWNEER COMPANY INC.


THESE DRAWINGS ARE THE SOLE AND EXCLUSIVE PROPERTY OF KAWNEER AND CONTAIN SENSITIVE, PRIVILEGED OR CONFIDENTIAL INFORMATION WHICH MAY BE USED ONLY FOR ITS BENEFIT. THE DISCLOSURE OF THESE DRAWINGS TO UNAUTHORIZED PERSONS IS STRICTLY PROHIBITED. THIS DOCUMENT AND ALL COPIES MUST BE RETURNED UPON DEMAND.
© COPYRIGHT KAWNEER COMPANY, INC., 2011

INSTALL 1" COVERS AT INTERMEDIATE MULLION LOCATIONS



VERSOLEIL OUTRIGGER
SUNSHADE
1600 SYSTEM 1
INSTALLATION INSTRUCTIONS

PIN VERTICAL COVER 2" BELOW BUTT JOINT WITH BRACKET CAP (494202). DRILL A Ø0.106 (#36 DRILL) HOLE THROUGH COVER AND PRESSURE PLATE LEG AND FASTEN WITH A #6 X 3/8" PHTF "B" FASTENER (128920).



WHEN VERSOLEIL OUTRIGGER SUNSHADES ARE INSTALLED ON THE FOLLOWING CORNER APPLICATIONS, COVER INSTALLATION IS THE SAME AS FOR INTERMEDIATE MULLION LOCATIONS:

- DOUBLE MULLION 90° OUTSIDE CORNER
- DOUBLE MULLION 90° INSIDE CORNER
- DOUBLE MULLION 135° OUTSIDE CORNER
- DOUBLE MULLION 135° INSIDE CORNER

INSTALLING THE SUNSHADES


ARRANGE THE SUNSHADE BAY ASSEMBLIES ON THE CONSTRUCTION SITE ACCORDING TO THEIR CORRESPONDING POSITION ON THE BUILDING. CHECK AGAINST SHOP DRAWINGS.

INSTALLATION CAN TAKE PLACE LEFT TO RIGHT OR RIGHT TO LEFT AS WELL AS TOP TO BOTTOM OR BOTTOM TO TOP (IN MULTIPLE STORY INSTALLATIONS). DEPENDING ON HOISTING METHOD, DETERMINE THE ORDER MOST APPROPRIATE FOR YOUR INSTALLATION. THE FOLLOWING INSTRUCTIONS WILL DEMONSTRATE A ONE-STORY INSTALLATION, RIGHT TO LEFT.

A. INSTALL FIRST BAY ASSEMBLY

HOIST AND POSITION THE FIRST SUNSHADE BAY ASSEMBLY UNTIL THE FOUR CLEAR HOLES ON BOTH OUTRIGGERS ALIGN WITH THE CORRESPONDING HOLES IN THE ANCHOR CLIPS. THE OUTRIGGERS SHOULD BE POSITIONED ON THE INSIDE OF THE ANCHOR CLIP. SEE DETAILS 7 AND 8. END ASSEMBLY WILL REQUIRE TEMPORARY FASTENER AT ANCHOR CLIP FILLER TO BE REMOVED JUST PRIOR TO ANCHORING. HOLD SPACER IN PLACE TO PREVENT IT FROM FALLING OUT OF POSITION.

NOTE:
VERSOLEIL OUTRIGGER SUNSHADE BAYS TO BE INSTALLED AFTER 1" COVERS.
VERSOLEIL OUTRIGGER SUNSHADE BAYS TO BE INSTALLED BEFORE OPTIONAL 3 1/8" COVERS. SEE PAGE 05 FOR OPTIONAL 3 1/8" COVER INSTALLATION.



IMPORTANT NOTE:
THE HOISTING METHOD SHOWN IS FOR ILLUSTRATION PURPOSES ONLY.
BE SURE TO FIRMLY SECURE THE SUNSHADE SO THAT IT CANNOT TILT, SLIDE OR SLIP FROM HOISTING STRAPS AND CHECK SAFETY GUIDELINES OF HOISTING EQUIPMENT BEFORE PROCEEDING.

THESE DRAWINGS ARE THE SOLE AND EXCLUSIVE PROPERTY OF KAWNEER AND CONTAIN SENSITIVE, PRIVILEGED OR CONFIDENTIAL INFORMATION WHICH MAY BE USED ONLY FOR ITS BENEFIT. THE DISCLOSURE OF THESE DRAWINGS TO UNAUTHORIZED PERSONS IS STRICTLY PROHIBITED. THIS DOCUMENT AND ALL COPIES MUST BE RETURNED UPON DEMAND.
© COPYRIGHT KAWNEER COMPANY, INC., 2011




**VERSOLEIL OUTRIGGER
SUNSHADE
1600 SYSTEM 1
INSTALLATION INSTRUCTIONS**

CONFIDENTIAL AND PROPRIETARY INFORMATION
KAWNEER COMPANY INC.

THESE DRAWINGS ARE THE SOLE AND EXCLUSIVE PROPERTY OF KAWNEER AND CONTAIN SENSITIVE, PRIVILEGED OR CONFIDENTIAL INFORMATION WHICH MAY BE USED ONLY FOR ITS BENEFIT. THE DISCLOSURE OF THESE DRAWINGS TO UNAUTHORIZED PERSONS IS STRICTLY PROHIBITED. THIS DOCUMENT AND ALL COPIES MUST BE RETURNED UPON DEMAND.
© COPYRIGHT KAWNEER COMPANY, INC., 2011

8




IMPORTANT NOTE:
DO NOT RELEASE HOISTING STRAPS (OR DISENGAGE OTHER LIFT APPARATUS) UNTIL SUNSHADE IS SECURED WITH ALL EIGHT BOLTS, AS DESCRIBED THROUGH "INSTALLING THE SUNSHADES"

SLIDE (2) 3/8" FLAT WASHERS (028596) PER BOLT ONTO THE 3/8" x 2" HEX HEAD BOLTS (128539) (NOTE: (2) WASHERS ARE REQUIRED TO CENTER BOLT ON MULLION). ON THE RIGHT SIDE (END ASSEMBLY), REMOVE THE TEMPORARY FASTENER AT ANCHOR CLIP FILLER (494201) AND ALIGN THE FILLER AND OUTRIGGER WITH THE ANCHOR CLIP. COMPLETELY SEAT THE RIGHT SET OF BOLTS AND FLAT WASHERS UNTIL THE FLAT WASHERS CONTACT THE SURFACE OF THE ANCHOR CLIP. ATTACH FOUR LOCK WASHERS (028779) AND FOUR 3/8" HEX NUTS (028780) TO THE RIGHT SET OF BOLTS. FINGER TIGHTEN. SEE DETAIL 10.


ON THE LEFT SIDE, INSERT FOUR 3/8" x 2" HEX HEAD BOLTS WITH FLAT WASHERS INTO ANCHOR CLIP AND THROUGH THE OUTRIGGERS. INSERT ANCHOR CLIP FILLER (494201) INTO THE CENTER OF THE ANCHOR CLIP AND CONTINUE INSERTING THE FOUR 3/8" x 2" HEX HEAD BOLTS UNTIL THE OUTER ENDS OF THE BOLTS ARE FLUSH WITH THE OUTSIDE SURFACE OF THE ANCHOR CLIP FILLER. SEE DETAIL 11. DO NOT COMPLETELY SEAT AND DO NOT ATTACH THE SECOND SET OF HEX NUTS.

TIGHTEN NUTS AT RIGHT SIDE. (DO NOT OVER TIGHTEN BOLTS. TIGHTEN TO A SNUG POSITION ENSURING THE SPRING TYPE LOCK WASHERS ARE COMPRESSED. THEN TIGHTEN APPROXIMATELY 1/2 TURN MORE).


9



10



11



VERSOLEIL OUTRIGGER
SUNSHADE
1600 SYSTEM 1
INSTALLATION INSTRUCTIONS


B. INSTALL SECOND BAY ASSEMBLY

NOTE: THE FOLLOWING INSTRUCTIONS APPLY TO THE BALANCE OF ALL INTERMEDIATE BAY ASSEMBLY INSTALLATIONS.

HOIST AND POSITION SUNSHADE BAY ASSEMBLY UNTIL THE (4) CLEAR HOLES OF THE OUTRIGGERS ALIGN WITH THE CORRESPONDING HOLES IN THE ANCHOR CLIPS. THE RIGHT SIDE SHOULD BE RELATIVELY TIGHT SINCE THE ANCHOR CLIP SPACER IS ALREADY IN POSITION. ON THE RIGHT SIDE, COMPLETELY SEAT THE (4) 3/8" HEX HEAD BOLTS AND (8) FLAT WASHERS (THROUGH THE OUTRIGGER AND ANCHOR CLIP). APPLY (4) LOCK WASHERS (028779) AND (4) HEX NUTS (028780) AND FINGER TIGHTEN. SEE BELOW.


ON THE LEFT SIDE, ALIGN AND INSERT AN ANCHOR CLIP FILLER (494201) INTO THE CENTER OF THE ANCHOR CLIP AND PARTIALLY SEAT ANOTHER SET OF (4) 3/8" x 2" HEX HEAD BOLTS AND (8) FLAT WASHERS. RUN BOLTS THROUGH ASSEMBLY UNTIL THE OUTER ENDS OF THE BOLTS ARE FLUSH WITH THE OUTSIDE SURFACE OF THE ANCHOR CLIP FILLER. DO NOT COMPLETELY SEAT AND DO NOT ATTACH THE SECOND SET OF HEX HEAD NUTS. SEE DETAIL BELOW.

AT RIGHT SIDE, MAKE MINOR ADJUSTMENTS HORIZONTALLY TO ALIGN ALL THE SUNSHADES WHILE TIGHTENING BOLTS AT THE ANCHOR CLIPS. (DO NOT OVER TIGHTEN BOLTS. TIGHTEN TO A SNUG POSITION ENSURING THE SPRING TYPE LOCK WASHERS ARE COMPRESSED. THEN TIGHTEN APPROXIMATELY 1/2 TURN MORE).



C. INSTALL FINAL BAY ASSEMBLY

ON THE FINAL BAY INSTALLATION (END ASSEMBLY), REMOVE THE TEMPORARY FASTENER AT ANCHOR CLIP FILLER (494201) AND ALIGN THE FILLER WITH THE ANCHOR CLIP AND COMPLETELY SEAT THE SET OF (4) BOLTS AND (8) FLAT WASHERS. APPLY (4) LOCK WASHERS (028779) AND (4) HEX NUTS (028780) AND FINGER TIGHTEN. SEE DETAIL BELOW.




MAKE MINOR ADJUSTMENTS HORIZONTALLY TO ALIGN ALL THE SUNSHADES WHILE TIGHTENING BOLTS AT THE ANCHOR CLIPS. (DO NOT OVER TIGHTEN BOLTS. TIGHTEN TO A SNUG POSITION ENSURING THE SPRING TYPE LOCK WASHERS ARE COMPRESSED. THEN TIGHTEN APPROXIMATELY 1/2 TURN MORE).

INSTALLING OPTIONAL 3 1/8" COVERS AT INTERMEDIATE MULLION LOCATIONS


INSTALL THE COVERS FROM THE BOTTOM OF THE ELEVATION UP. ALIGN THE LOWER COVER ON THE MULLION WITH THE 1.013" X 6" NOTCH AT THE TOP AND ENGAGE COVER. THE SPLICE SLEEVE (162566) MUST BE SET INTO SEALANT AT THE TOP OF THE LOWER COVER ABOVE THE SUNSHADE, AFTER THE LOWER COVER HAS BEEN ENGAGED.

NOTE: THE 3/8" HEX HEAD BOLTS AND CORRESPONDING NUTS MUST BE CENTERED ON THE ANCHOR CLIP IN ORDER FOR THE SPLICE SLEEVE TO FIT. CHECK AND MAKE ADJUSTMENTS BEFORE PROCEEDING.


APPLY HORIZONTAL COVERS PER STANDARD INSTALLATION INSTRUCTIONS.



ALIGN THE UPPER COVER WITH THE MULLION, ABOVE THE OUTRIGGERS, AND SPLICE SLEEVE ON THE LOWER COVER, LEAVING A 1/2" EXPANSION SPLICE BETWEEN THE UPPER AND LOWER COVERS. ENGAGE AS PER STANDARD 1600 SYSTEM 1 INSTALLATION INSTRUCTIONS.



AT ALL VERTICAL COVER LOCATIONS, PIN BOTH HALVES OF THE VERTICAL COVERS. DRILL A .106" DIAMETER HOLE (#36 DRILL) 2" BELOW THE SPLICE AND 2 7/16" FROM THE OUTSIDE SURFACE OF THE COVER. INSTALL #6 x 3/8" PAN HEAD SCREWS (128920).



SUNSHADE ATTACHMENT - CORNERS


ASSEMBLING THE CORNER SUNSHADES

VERSOLEIL OUTRIGGER SUNSHADE BAY ASSEMBLIES USE SCREW SPLINE JOINERY. LAYOUT LEFT AND RIGHT OUTRIGGERS (INSIDE CORNERS AND SINGLE MULLION 90° OUTSIDE CORNERS ARE HANDED PARTS), BLADES, AND FASCIA PER SHOP DRAWINGS. SEE BELOW.

USING #12-24 X 1" FLAT HEAD THREAD CUTTING SCREWS (128555), JOIN BLADES AND FASCIA TO CORNER OUTRIGGER - DO NOT TIGHTEN COMPLETELY. USING #12-24 x 1" PAN HEAD THREAD CUTTING SCREWS (128556), JOIN BLADES AND FASCIA COMPONENTS TO TYPICAL INTERMEDIATE OUTRIGGER. TIGHTEN SCREWS ON BOTH SIDES.

NOTE: WHEN ASSEMBLING 135° OUTSIDE CORNER, THE USE OF A #12-24 X 3/4" FHTCMS (128107) FASTENER IS REQUIRED AT THE INNER-MOST BLADE DUE TO THE LENGTH OF THE BLADE AT THIS LOCATION. SEE BELOW.

ASSEMBLE ALL OF THE VERSOLEIL OUTRIGGER SUNSHADE BAY ASSEMBLIES AND MARK OR TAG EACH ONE TO MATCH CORRESPONDING UNIT AS SHOWN ON SHOP DRAWINGS.



VERSOLEIL OUTRIGGER
SUNSHADE
1600 SYSTEM 1
INSTALLATION INSTRUCTIONS

95494-24
09/05/11

494970 (SHEET 06 OF 13)

ATTACH ANCHOR CLIPS AT 90° SINGLE MULLION OUTSIDE CORNER LOCATIONS


NOTE: OPTIONAL 3 1/8" COVERS WILL BE INSTALLED AFTER THE VERSOLEIL OUTRIGGER SUNSHADE BAY ASSEMBLIES. REFER TO PAGE 11 FOR INSTALLATION DETAILS.

1" COVERS MUST BE INSTALLED AFTER THE ANCHOR CLIPS HAVE BEEN INSTALLED.

THE 90° O/S SINGLE MULLION SUPPORT (494206) IS TO BE INSTALLED USING TWO 1/4 X 1 3/4" HWHTF "AB" SCREWS (128960). AFTER INSTALLATION, RUN A BEAD OF SEALANT INSIDE THE SINGLE MULLION SUPPORT (AND TONGUES OF MULLION AT BRACKET LOCATIONS), ALIGN LARGE SLOTS IN THERMAL TONGUE FILLER (494211) WITH LARGE MOUNTING HOLES IN THE SINGLE MULLION SUPPORT AND TAP INTO PLACE. ADJUST TONGUE FILLER UNTIL LARGE SLOTS ARE IN PROPER ALIGNMENT WITH SINGLE MULLION SUPPORT MOUNTING HOLES. SEAL AROUND TONGUE FILLER SPLICES AND INSTALL CORNER PRESSURE PLATE IN ACCORDANCE WITH STANDARD INSTALLATION INSTRUCTIONS.

AFTER PRESSURE PLATES ARE INSTALLED, APPLY ANCHOR CLIPS AS SHOWN BELOW. TIGHTEN BOLTS TO A "SNUG" CONDITION AND COMPLETELY COMPRESS THE SPRING TYPE LOCK WASHERS. THEN TIGHTEN APPROXIMATELY 1/2 TURN MORE.

NOTE: DO NOT INCREASE HOLE SIZE TO FACILITATE INSTALLATION.




INSTALLING 1" COVERS AT 90° SINGLE MULLION OUTSIDE CORNER LOCATIONS


THE 90° SINGLE MULLION CORNER COVERS CAN BE INSTALLED EITHER TOP DOWN, OR BOTTOM UP IF THE BRACKET CAPS (494212 & 494213) ARE INSTALLED FIRST. THE BRACKET CAPS SHOULD BE ALIGNED WITH THE MULLION AND CENTERED ON THE ANCHOR CLIPS AND ENGAGE.

THE LOWER COVERS SHOULD BE BUTTED TO THE BOTTOM OF THE BRACKET CAPS (494212 & 494213) AND ENGAGED PER STANDARD INSTALLATION INSTRUCTIONS.

THE UPPER COVERS SHOULD BE SET WITH A 1/2" EXPANSION SPLICE BETWEEN THE TOP OF THE BRACKET CAPS AND THE BOTTOM OF THE UPPER COVERS, AND ENGAGED PER STANDARD INSTALLATION INSTRUCTIONS.



PIN VERTICAL COVER 2" BELOW BUTT JOINT WITH BRACKET CAP (494212 / 494213). DRILL A Ø0.106 (#36 DRILL) HOLE THROUGH COVER AND PRESSURE PLATE LEG AND FASTEN WITH A #6 X 3/8" PHTF "B" FASTENER (128920).



CONTINUE INSTALLING COVERS AS DESCRIBED IN PREVIOUS STEPS.

494970 (SHEET 07 OF 13)

CONFIDENTIAL AND PROPRIETARY INFORMATION
KAWNEER COMPANY INC.

THESE DRAWINGS ARE THE SOLE AND EXCLUSIVE PROPERTY OF KAWNEER AND CONTAIN SENSITIVE, PRIVILEGED OR CONFIDENTIAL INFORMATION WHICH MAY BE USED ONLY FOR ITS BENEFIT. THE DISCLOSURE OF THESE DRAWINGS TO UNAUTHORIZED PERSONS IS STRICTLY PROHIBITED. THIS DOCUMENT AND ALL COPIES MUST BE RETURNED UPON DEMAND.
© COPYRIGHT KAWNEER COMPANY, INC., 2011


INSTALLING ANCHOR CLIPS AND 1" COVERS AT 135° SINGLE MULLION OUTSIDE CORNER LOCATIONS

NOTE: OPTIONAL 3 1/8" COVERS WILL BE INSTALLED AFTER THE VERSOLEIL OUTRIGGER SUNSHADE BAY ASSEMBLIES. REFER TO PAGE 11 FOR INSTALLATION DETAILS.

INSTALL (2) ANCHOR CLIPS SIMILAR TO 90° SINGLE MULLION OUTSIDE CORNER WITHOUT CENTER CLIP.

COVERS SHOULD BE INSTALLED AFTER THE ANCHOR CLIPS HAVE BEEN INSTALLED.

THE COVER BELOW THE ANCHOR CLIP SHOULD BE SNAPPED INTO PLACE FIRST.




KAWNEER

VERSOLEIL OUTRIGGER
SUNSHADE
1600 SYSTEM 1
INSTALLATION INSTRUCTIONS


95494-24
09/05/11

494970 (SHEET 07 OF 13)

BRACKET CAP (494214) SHOULD BE SNAPPED INTO PLACE, OVER THE ANCHOR CLIPS.



THE COVER ABOVE THE ANCHOR CLIP SHOULD BE SNAPPED INTO PLACE, LEAVING A 1/2" EXPANSION JOINT.



PIN VERTICAL COVER 7" BELOW BUTT JOINT WITH BRACKET CAP (494214). DRILL A Ø0.106 (#36 DRILL) HOLE THROUGH COVER AND PRESSURE PLATE LEG AND FASTEN WITH A #6 X 3/8" PHTF "B" FASTENER (128920).

PIN BRACKET CAP (494214) 2" BELOW 1/2" SPLICE. DRILL A Ø0.106 (#36 DRILL) HOLE THROUGH CAP AND PRESSURE PLATE LEG AND FASTEN WITH A #6 X 3/8" PHTF "B" FASTENER (128920).

INSTALLING ANCHOR CLIPS AND 1" COVERS AT 135° DOUBLE MULLION OUTSIDE CORNER LOCATIONS

INSTALL ANCHOR CLIPS AND 1" COVERS SIMILAR TO TYPICAL INTERMEDIATES.

INSTALLING THE SUNSHADE AT 90° SINGLE MULLION OUTSIDE CORNERS

IF THE SUNSHADE APPLICATION INCLUDES AN OUTSIDE CORNER, CONTINUE TO INSTALL SUNSHADES AS PREVIOUSLY DESCRIBED APPROACHING THE OUTSIDE CORNER CONDITION.

A) MOVE ONE CORNER BAY INTO THE "OUTER" ANCHOR CLIP. ATTACH OUTRIGGER TO ANCHOR CLIP (494200) USING 3/8"-16 X 2" BOLTS (128539), 3/8" FLAT WASHERS (028596), 3/8" LOCK WASHERS (028779) AND 3/8" HEX NUTS (028780). TIGHTEN BOLTS AT 494200 ANCHOR CLIP TO A "SNUG" CONDITION AND COMPLETELY COMPRESS THE SPRING TYPE LOCK WASHERS, THEN TIGHTEN APPROXIMATELY 1/2 TURN MORE.

ATTACH CORNER OUTRIGGER TO SINGLE MULLION 90° CENTER ANCHOR CLIP (494217) USING 3/8"-16 X 1" BOLTS (028969) AND 3/8" LOCK WASHERS (028779). TIGHTEN ALL BOLTS AT SM 90° CENTER ANCHOR CLIP TO A SNUG POSITION ENSURING THE SPRING TYPE LOCK WASHERS ARE COMPRESSED.

****DO NOT EXCEED 100 IN-LBS OF TORQUE****

B) INSTALL SECOND CORNER BAY IN THE SAME MANNER AS THE FIRST.

C) INSERT 90 OUTSIDE CORNER SPACER (494241) BETWEEN CORNER OUTRIGGERS AND SECURE USING (1) 1/4-20 X 1 3/4" HWHMS, (1) LOCK WASHER (128974), AND (1) 1/4-20 HEX NUT (977099).

D) CONTINUE INSTALLING SUNSHADES AS DESCRIBED IN PREVIOUS STEPS.

SEE BELOW FOR CENTER ANCHOR CLIP DETAILS


ANCHOR CLIP FILLER (494201)

NOTE THAT AT 90° SINGLE MULLION CORNER ONLY, THE CORNER OUTRIGGER IS LOCATED ON THE OUTSIDE OF THE ANCHOR CLIP

1/4" LOCK WASHER (128974)
1/4 - 20 NUT (977099)

1/4 - 20 x 1-3/4" HWHMS (128991)

90 OUTSIDE CORNER SPACER (494241)



KAWNEER VERSOLEIL OUTRIGGER
SUNSHADE
1600 SYSTEM 1
INSTALLATION INSTRUCTIONS

95494-30
02/17/12

494970 (SHEET 08 OF 13)

494970 (SHEET 08 OF 13)


CONFIDENTIAL AND PROPRIETARY INFORMATION
KAWNEER COMPANY INC.

THESE DRAWINGS ARE THE SOLE AND EXCLUSIVE PROPERTY OF KAWNEER AND CONTAIN SENSITIVE, PRIVILEGED OR CONFIDENTIAL INFORMATION WHICH MAY BE USED ONLY FOR ITS BENEFIT. THE DISCLOSURE OF THESE DRAWINGS TO UNAUTHORIZED PERSONS IS STRICTLY PROHIBITED. THIS DOCUMENT AND ALL COPIES MUST BE RETURNED UPON DEMAND.
© COPYRIGHT KAWNEER COMPANY, INC., 2011


**INSTALLING THE SUNSHADE AT 135 ° SINGLE MULLION
OUTSIDE CORNERS**

IF THE SUNSHADE APPLICATION INCLUDES AN OUTSIDE CORNER, CONTINUE TO INSTALL SUNSHADES AS PREVIOUSLY DESCRIBED APPROACHING THE OUTSIDE CORNER CONDITION.

- A) INSTALL ONE SIDE OF CORNER SIMILAR TO "STRAIGHT RUN" OF SUNSHADE, USING CORNER ANCHOR CLIP FILLER (494201) AT THE CORNER MULLION.
- B) THE SECOND SIDE OF THE CORNER WILL BE LOWERED INTO THE ANCHOR CLIPS (494200) THEN FASTENED AS DESCRIBED IN THE "STRAIGHT RUN" SECTION.




- C) SECURE FIRST CORNER SUNSHADE ASSEMBLY TO SECOND SUNSHADE ASSEMBLY USING 1/4"-20 x 1-1/2" HWHMS (128333), OUTSIDE CORNER SPACER (494210), 1/4" HELICAL LOCK WASHER (128974), AND 1/4"-20 HEX NUT-MS (977099) AT (6) LOCATIONS FOR 36" DEPTH SUNSHADE OR (4) LOCATIONS FOR 30" DEPTH SUNSHADE.
- D) CONTINUE INSTALLING SUNSHADES AS DESCRIBED IN PREVIOUS STEPS.




**INSTALLING THE SUNSHADE AT 90° & 135 ° DOUBLE
MULLION INSIDE CORNERS**

IF THE SUNSHADE APPLICATION INCLUDES AN INSIDE CORNER, CONTINUE TO INSTALL SUNSHADES AS PREVIOUSLY DESCRIBED APPROACHING THE INSIDE CORNER CONDITION.

- A) INSTALL ONE SIDE OF CORNER SIMILAR TO "STRAIGHT RUN" OF SUNSHADE, USING CORNER ANCHOR CLIP FILLER (494205) AT THE CORNER MULLION.
- B) THE SECOND SIDE OF THE CORNER WILL BE LOWERED INTO THE ANCHOR CLIPS (494200) THEN FASTENED AS DESCRIBED IN THE "STRAIGHT RUN" SECTION, USING THE CORNER ANCHOR CLIP FILLER (494205) AT THE CORNER MULLION.
- C) CONTINUE INSTALLING SUNSHADES AS DESCRIBED IN PREVIOUS STEPS.





INSTALLING THE SUNSHADE AT 90° & 135 ° DOUBLE MULLION OUTSIDE CORNERS


IF THE SUNSHADE APPLICATION INCLUDES AN OUTSIDE CORNER, CONTINUE TO INSTALL SUNSHADES AS PREVIOUSLY DESCRIBED APPROACHING THE OUTSIDE CORNER CONDITION.

FOR CORNER BRAKE CLOSURE ATTACHMENT, 027972 ANGLES MAY NEED TO BE PRE-APPLIED TO THE PRESSURE PLATE PRIOR TO INSTALLING PRESSURE PLATE IF ACCESS IS TOO TIGHT TO MATCH DRILL PRESSURE PLATE. REFERENCE SHOP DETAILS. MATCH DRILL .154 DIA. [#23 DRILL] HOLES IN PRESSURE PLATE LEG AND APPLY WITH 128407 #10 x 7/16" PH SCREWS.

USING PRE-DRILLED MOUNTING HOLES, INSTALL A TAPPING BAR (494204) ON EACH CORNER MULLION USING 1/4"-20 X 3/4" FHMS (128925). INSTALL OUTSIDE CORNER ANCHOR STEM (494208 - 90° CORNER; 494209 - 135° CORNER) USING 3/8"-16 X 1" BOLT (028969), 3/8" LOCK WASHER (028779) AND SEPARATORS (027477) BETWEEN STEEL ANCHOR STEM AND ALUMINUM TAPPING BARS. TIGHTEN 3/8" BOLTS TO A "SNUG" CONDITION ENSURING SPRING TYPE LOCK WASHERS ARE COMPLETELY COMPRESSED.
****DO NOT EXCEED 100 IN-LBS****

INSTALL ONE SIDE OF CORNER SIMILAR TO "STRAIGHT RUN" OF SUNSHADE, ATTACHING TO ANCHOR CLIP (494200) AND OUTSIDE CORNER ANCHOR STEM (494208 - 90° CORNER; 494209 - 135° CORNER) USING 3/8"-16 X 2" BOLT (128539), 3/8" FLAT WASHER (028596), 3/8" LOCK WASHER (028779), 3/8" HEX NUT (028780) AND SEPARATOR (027477) BETWEEN STEEL ANCHOR STEM AND ALUMINUM OUTRIGGER.

INSTALL SECOND SIDE OF CORNER IN THE SAME MANNER AS THE FIRST, ATTACHING TO ANCHOR CLIP (494200) AND OUTSIDE CORNER ANCHOR STEM (494208 - 90° CORNER; 494209 - 135° CORNER) USING 3/8"-16 X 2" BOLT (128539), 3/8" FLAT WASHER (028596), 3/8" LOCK WASHER (028779), 3/8" HEX NUT (028780) AND SEPARATOR (027477) BETWEEN STEEL ANCHOR STEM AND ALUMINUM OUTRIGGER.




VERSOLEIL OUTRIGGER
SUNSHADE
1600 SYSTEM 1
INSTALLATION INSTRUCTIONS

FIELD BOND ANGLE (027150) AND BRAKE METAL BACK-UP ANGLES TO CORNER BRAKE METAL, AS SHOWN BELOW. LOWER BRAKE METAL MUST BE MANEUVERED INTO POSITION SO THAT NOTCH FITS AROUND CORNER OUTRIGGERS. USING BREAK METAL AS A GUIDE, MATCH DRILL PERIMETER CHANNELS WITH Ø0.159 (#21 DRILL) HOLES AND FASTEN TO PERIMETER CHANNELS USING #10 X 7/16" B PHTF FASTENERS (128407) ON 24" CENTERS. ALLOW A 1/2" EXPANSION SPLICE BETWEEN UPPER AND LOWER BRAKE METAL.

CLEAN AND PRIME (AS REQUIRED) ALL AREAS AROUND SPLICE PER SEALANT MANUFACTURER'S RECOMMENDATIONS. INSERT BACKER ROD AT BRAKE METAL SPLICE INTO ALL GAPS AROUND CORNER OUTRIGGERS AND INTO 1/2" EXPANSION SPLICE AND FILL WITH SEALANT. TOOL SEALANT.


CONTINUE INSTALLING SUNSHADES AS DESCRIBED IN PREVIOUS STEPS.



INSTALLING OPTIONAL 3 1/8" COVERS AT SINGLE MULLION 90° OUTSIDE CORNERS

THE 90° SINGLE MULLION OUTSIDE CORNER COVERS HAVE BEEN SPLIT INTO AN UPPER PIECE AND A LOWER PIECE, AND MUST BE INSTALLED FROM THE BOTTOM OF THE ELEVATION UP. THE TOP OF THE LOWER COVER IS NOTCHED. ALIGN THE COVER ON THE MULLION WITH THE NOTCH FACING UP. THE LOWER COVERS SHOULD BE MANEUVERED INTO POSITION AND SNAPPED IN PLACE. FIELD BOND THE SPLICE SLEEVE (162570) TO THE TOP OF THE LOWER COVERS.

PIN BOTH HALVES OF THE VERTICAL COVERS. DRILL A Ø0.106" HOLE (#36 DRILL) 2" BELOW THE SPLICE AND 2 11/16" FROM THE OUTSIDE SURFACE OF THE COVER. INSTALL #6 x 3/8" PAN HEAD SCREWS (128920).




THESE DRAWINGS ARE THE SOLE AND EXCLUSIVE PROPERTY OF KAWNEER AND CONTAIN SENSITIVE, PRIVILEGED OR CONFIDENTIAL INFORMATION WHICH MAY BE USED ONLY FOR ITS BENEFIT. THE DISCLOSURE OF THESE DRAWINGS TO UNAUTHORIZED PERSONS IS STRICTLY PROHIBITED. THIS DOCUMENT AND ALL COPIES MUST BE RETURNED UPON DEMAND.
© COPYRIGHT KAWNEER COMPANY, INC., 2011



THE UPPER COVERS SHOULD BE MANEUVERED INTO POSITION, AND OVER THE SPLICE SLEEVES, LEAVING A 1/2" SPLICE BETWEEN THE LOWER COVER AND THE UPPER COVER. THE UPPER COVERS SHOULD BE ENGAGED PER STANDARD INSTALLATION INSTRUCTIONS.

NOTE: THE 3/8" HEX HEAD BOLTS AND CORRESPONDING NUTS MUST BE CENTERED ON THE ANCHOR CLIP IN ORDER FOR THE SPLICE SLEEVE TO FIT. CHECK AND MAKE ADJUSTMENTS BEFORE PROCEEDING.


APPLY HORIZONTAL COVERS PER STANDARD INSTALLATION INSTRUCTIONS.



**INSTALLING OPTIONAL 3 1/8" COVERS AT SINGLE MULLION
135° OUTSIDE CORNERS**

IF THE SUNSHADE APPLICATION INCLUDES A SINGLE MULLION 135° OUTSIDE CORNER, CONTINUE TO INSTALL SUNSHADES AS PREVIOUSLY DESCRIBED APPROACHING THE OUTSIDE CORNER CONDITION.


THE 135° SINGLE MULLION CORNER COVERS CAN BE INSTALLED EITHER TOP DOWN OR BOTTOM UP IF THE BRACKET CAP (494216) IS INSTALLED FIRST. THE BRACKET CAP (494216) SHOULD BE ALIGNED WITH THE MULLION AND SLID DOWN OVER THE OUTRIGGERS, ALLOWING THE BRACKET CAP TO REST ON THE TOP OF THE OUTRIGGERS, THEN ENGAGED.



THE LOWER COVER SHOULD BE BUTTED TO THE BOTTOM OF THE BRACKET CAP (494216) AND ENGAGED PER STANDARD INSTALLATION INSTRUCTIONS.

THE UPPER COVER SHOULD BE SET WITH A 1/2" EXPANSION GAP BETWEEN THE BRACKET CAP (494216) AND THE UPPER COVER, AND ENGAGED PER STANDARD INSTALLATION INSTRUCTIONS.

CONTINUE INSTALLING SUNSHADE COVERS AS DESCRIBED IN PREVIOUS STEPS.



PIN THE VERTICAL COVERS AND CAPS. DRILL A Ø0.106" HOLE (#36 DRILL) 2" BELOW THE 1/2" EXPANSION SPLICE & 2" BELOW THE BUTT JOINT AND 2 5/8" FROM THE OUTSIDE SURFACE OF THE COVER. INSTALL #6 x 3/8" PAN HEAD SCREWS (128920).

INSTALLING OPTIONAL 3 1/8" COVERS ON 90° & 135° DOUBLE MULLION OUTSIDE & INSIDE CORNERS

WHEN DEEP COVERS ARE USED WITH THE VERSOLEIL OUTRIGGER SUNSHADE, THE COVERS WILL BE FACTORY PREPPED AND SHIPPED READY TO INSTALL. DOUBLE MULLION CORNER COVERS WILL BE INSTALLED IN THE SAME MANNER AS FOR INTERMEDIATE MULLIONS.

NOTE: DOUBLE MULLION 90° AND 135° CORNER COVERS WILL HAVE A RH/LH BOTTOM COVER, REFER TO APPROVED SHOP DRAWINGS TO DETERMINE PROPER ORIENTATION OF NOTCHES.

THESE DRAWINGS ARE THE SOLE AND EXCLUSIVE PROPERTY OF KAWNEER AND CONTAIN SENSITIVE, PRIVILEGED OR CONFIDENTIAL INFORMATION WHICH MAY BE USED ONLY FOR ITS BENEFIT. THE DISCLOSURE OF THESE DRAWINGS TO UNAUTHORIZED PERSONS IS STRICTLY PROHIBITED. THIS DOCUMENT AND ALL COPIES MUST BE RETURNED UPON DEMAND.
© COPYRIGHT KAWNEER COMPANY, INC., 2011



VERSOLEIL OUTRIGGER
SUNSHADE
1600 SYSTEM 1
INSTALLATION INSTRUCTIONS